

CONTEC

Stock Code:300869



LIGHT THE RHYTHM OF LIFE WITH TECHNOLOGY



Electrocardiograph E6

Contec Medical Systems Co.,Ltd.

ADD:No.112 Qinhuang West Street, Economic & Technical Development Zone,
Qinhuangdao, Hebei Province, PEOPLE'S REPUBLIC OF CHINA

Tel: +86-335-8015430

Fax: +86-335-8015588

E-mail: cms@contecmed.com.cn

Website: <http://www.contecmed.com>

CONTEC reserves the right of product appearance, specifications and function modification and updating,
without prior notification. CMS2.782.538EXC/1.0 1.4.03.11.132

Electrocardiograph

E6



12-channel ECG



Portable design



Auto-analysis report



Accurate in measurement



Time print



Rechargeable lithium battery



This product is an electrocardiograph which is able to collect 12-lead ECG signals simultaneously and print out the ECG waveform with thermal printing system. Its functions are as follows: recording and displaying ECG waveform in auto/manual mode; measuring ECG waveform parameters automatically, and automatic analysis and diagnosis; ECG pace maker detection; electrode-off and out of paper warning; optional interface languages (Chinese/English, etc.); built-in lithium battery, powered either by AC or DC; you can willingly select the rhythm lead to conveniently observe abnormal heart rate; case database management, etc.

Function

- ◆ Adopt 7" high-resolution color LCD, operate by touch screen and function buttons, convenient to use.
- ◆ Sync collection for 12-lead ECG, support routine 12-lead and Cabrera-lead waveform display. Get high-quality ECG waveform via AC filter, DFT filter, EMG filter and Low-pass Filter of ECG signal.
- ◆ Display 3/6/12 - lead ECG waveform, print mode, sensitivity, paper speed, filter status, etc. on one screen, convenient for contrastively diagnosing.
- ◆ Power supply: AC/DC, with built-in rechargeable lithium battery, charging circuit, perfect over-current and over-voltage protection circuit.
- ◆ Support many print modes like auto 1*12, auto 2*6, auto 2*6+1, auto 3*4, auto 3*4+1, auto 4*3, auto 4*3+1, auto 6*2, auto 6*2+1, rhythm 7, rhythm 6, rhythm 5, rhythm 4, rhythm 3, rhythm 2 and manual. The printed content contains time, calibration signal, filter status and patient's information. Information including printed waveform length, output measurement parameters, diagnostic conclusion, superposition QRS wave, histogram, trend chart, interval list can be set, and with time print function, which meets different kinds of requirement.
- ◆ With the functions of auto-measurement and auto-interpretation for routine ECG parameters, it can provide measurement results for HR, PR interval, P Duration, QRS Duration, T Duration, QT/QTc interval, P/QRS/T Axis, R(V5), S(V1) and R(V5)+S(V1), etc. and auto-diagnosis conclusion, which can reduce the doctor's burden a lot.
- ◆ Rhythm lead can be selected freely, convenient to observe abnormal heart rhythm.
- ◆ The testee's clinical information (such as, ID, Name, Age, Sex, Height, Weight, etc.) can be entered.
- ◆ 1000 cases (3 s case is frequently used) can be stored by the built-in memory, convenient for case review and statistic.
- ◆ In optimal DC state, up to 10-hour standby time, continuous print for more than 3-hour and print up to 1000 ECG waveform (3 s case is frequently used).
- ◆ Multi-language (Chinese, English, Turkish, Portuguese, German, Russian and Kazakh, etc.) interface and report.